

Double Dragon Spring Hanger Data Sheet



Product Description

A wide range of double steel spring hangers offering the optimum performance for low frequency vibration Isolation. Comprehensive load ranges and different fixing requirements offered.

Design Features

Electro Painted steel frame with other steel parts being HDG or Powder Coated

Helical Steel Springs, colour coded and manufactured in the UK to BS1726 with nominal deflection up to 50mm

Includes bespoke 12mm dampening arrangement including rubber block.

Pre-compression of spring possible before installation and can be delivered pre-set for ease of installation

Fitting via drop rod or direct to supporting structure.

M16 threaded rod for connection to pipework with 15 degs of allowable angulation

50% Overload capacity

Applications


- Pipework & Ductwork
- Suspended Plant
- Axial Fans & Fan Coil units
- Acoustic Ceilings



FRONT VIEW



SIDE VIEW



TOP VIEW

Part Number	Load (Kg)	Static Deflection (mm)	Spring Colour
DoubleDragon-250-50	250	50	BROWN
DoubleDragon-300-50	300	50	BLUE
DoubleDragon-400-50	400	50	WHITE
DoubleDragon-500-50	500	50	BLACK
DoubleDragon-600-50	600	50	PINK
DoubleDragon-800-50	800	50	PURPLE