

Friction Anchor with Thermal Break






Product Description

Designed to stop axial, lateral and vertical movement of pipe. Thermal break pad included. These can be floor, ceiling or wall mounted. Designed with height adjustable to aid installation.

Using Sikla FPC to avoid having to use Pipe Stops - Up to allowable forces as listed below

For use on Horizontal Pipe runs only



Design Features

- High Performance Coatings EP&ZN
- Easy height adjustment with "NS Socket Technology"
- Reduced heat loss with thermal break (included)
- For steel pipe sizes DN100-DN350
- 200,250 and 300NB come with MPC (Included)
- FPC Clip provided in BZP finish

Please refer to installation instructions for full details

Part Number	Connection to Clamp	LOAD - Axial	LOAD - Vertical	LOAD - Lateral
NS-PAPDI-100-FA	4 x M16	10kN	10kN	10kN
NS-PAPDI-125-FA	4 x M16	10kN	10kN	10kN
NS-PAPDI-150-FA	4 x M16	10kN	10kN	10kN
NS-PAPDI-200-FA	4 x M16	10kN	10kN	10kN
NS-PAPDI-250-FA	4 x M16	10kN	10kN	10kN
NS-PAPDI-300-FA	4 x M16	10kN	10kN	10kN
NS-PAPDI-350-FA	4 x M16	10kN	10kN	10kN

Please note this document can be subject to alteration without notification. Issue 15.01.25