

PAPi Pipe Anchor with Thermal Break (Copper)








Product Description

Designed to stop axial, lateral and vertical movement of pipe with a Thermal Break Pad to isolate the pipework from cold bridging. These can be floor, ceiling or wall mounted. Designed with height adjustable to aid installation.

Design Features

- High Performance Coatings EP&ZN
- Easy height adjustment with "NS Socket Technology"
- Reduced heat loss with Thermal Break (Included)
- EP Clips Supplied to avoid issues with dissimilar metals
- For Copper or Stainless S pipes 54-159mm OD
- Suitable for use on below ambient services
- Recommended that Pipe Stops are used, please refer to install instructions



Part Number	Clip to fit pipe OD (mm)	Max Temp	Load Axial	Load Vertical	Load Lateral
NS-PAPi-CU-15mm	15	200	9kN	9kN	9kN
NS-PAPi-CU-22mm	22	200	9kN	9kN	9kN
NS-PAPi-CU-28mm	28	200	9kN	9kN	9kN
NS-PAPi-CU-35mm	35	200	9kN	9kN	9kN
NS-PAPi-CU-42mm	42	200	9kN	9kN	9kN
NS-PAPi-CU-54mm	54	200	9kN	9kN	9kN
NS-PAPi-CU-67mm	67	200	9kN	9kN	9kN
NS-PAPi-CU-76mm	76	200	9kN	9kN	9kN